

SABRE AIRCRAFT TOOLS

Torque Control Shut-Off Screwdrivers STC05 Series



Model No.	Free Speed RPM	Torque Range In-lbs (Nm)	Air Consumption CFM (L/Min)	Length inch (mm)	Weight Lbs (kg)	Noise Level dB(A)	Vibration Level
S26020	1800	3~26 (0.3~2.9)	4 (113)	8.7" (220mm)	2.0lbs (0.9kg)	83	<2.5m/s ²
S26025	1000	3~40 (0.4~4.5)	4 (113)	8.7" (220mm)	2.0lbs (0.9kg)	83	<2.5m/s ²
S26030	600	4~45 (0.5~5.1)	4 (113)	8.7" (220mm)	2.0lbs (0.9kg)	83	<2.5m/s ²

Comes standard with 2 extra torque springs.

Optional Accessories:



#SPA26025
Cam Assembly



#SPA26030
Cam Assembly



#SPA26035
Cam Assembly



In/Lbs 10-38
Nm (1.1 - 4.3)
Yellow

#SP26050



In/Lbs 5-19
Nm (0.6 - 2.1)
Black

#SP26055



In/Lbs 2-8
Nm (0.23 - 0.9)
Green

#SP26060

Operating Air Pressure: 90 PSI / 6.2 bar.
Air Inlet Size: 1/4"

Safety Precaution: Read and follow all safety and operating instructions.

WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com
info@sabretools.com