

# SABRE AIRCRAFT TOOLS

## Oil Pulse Tools



### 1/4" HEX PISTOL GRIP TORQUE CONTROL SHUT-OFF

Model No.	Torque Range Ft-Lbs (Nm)	Bolt Capacity Inch (mm)	Free Speed RPM	Length Inch (mm)	Weight Lbs (kg)	Noise Level dB(A)	Vibration Level
S26105	3.0 - 5.9 (4-8)	3/16" (M5)	6,500	6.77" (172mm)	2.2lbs (1.0kg)	78	<2.0m/s <sup>2</sup>
S26106	3.7 - 7.4 (5-10)	1/4" (M6)	6,500	7.0" (178mm)	2.2lbs (1.0kg)	78	<2.0m/s <sup>2</sup>
S26107	5.9 - 10.3 (8-14)	1/4" (M6)	6,500	7.13" (181mm)	2.2lbs (1.0kg)	79	<2.1m/s <sup>2</sup>
S26108	8.9 - 14.8 (12-20)	5/16" (M8)	6,000	7.64" (194mm)	2.8lbs (1.3kg)	79	<2.2m/s <sup>2</sup>
S26109	14.8 - 23.6 (20-32)	3/8" (M10)	6,000	7.56" (192mm)	3.3lbs (1.5kg)	80	<2.5m/s <sup>2</sup>

### 1/4" HEX PISTOL GRIP TORQUE CONTROL NON SHUT-OFF

Model No.	Torque Range Ft-Lbs (Nm)	Bolt Capacity Inch (mm)	Free Speed RPM	Length Inch (mm)	Weight Lbs (kg)	Noise Level dB(A)	Vibration Level
S26125	4.4 - 8.9 (6-12)	1/4" (M6)	6,500	5.43" (138mm)	1.9lbs (0.87kg)	78	<2.0m/s <sup>2</sup>
S26126	7.4 - 11.8 (10-16)	1/4" (M6)	6,500	5.83" (148mm)	2.1lbs (0.97kg)	78	<2.0m/s <sup>2</sup>
S26127	11.1 - 25.8 (12-35)	5/16" (M8)	6,500	6.14" (156mm)	2.2lbs (1.0kg)	79	<2.1m/s <sup>2</sup>
S26128	18.4 - 29.5 (25-40)	3/8" (M10)	6,000	6.46" (164mm)	2.2lbs (1.0kg)	79	<2.2m/s <sup>2</sup>
S26129	22.1 - 33.2 (30-45)	3/8" (M10)	6,000	6.65" (169mm)	2.86lbs (1.3kg)	80	<2.5m/s <sup>2</sup>

\* Torque Range (Hard Joint Rotatory Measure) @ 5 ~ 6 BAR (72.5 ~ 87 PSI)

Operating Air Pressure: 90 PSI / 6.2 bar.  
Air Inlet Size: 1/4"

**Safety Precaution:** Read and follow all safety and operating instructions.

**WARNING:** Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com  
info@sabretools.com