

SABRE AIRCRAFT TOOLS

Oil Pulse Tools



3/8" SQUARE PISTOL GRIP TORQUE CONTROL SHUT-OFF

| Model No. | Torque Range Ft-Lbs (Nm) | Bolt Capacity Inch (mm) | Free Speed RPM | Length Inch (mm) | Weight Lbs (kg) | Noise Level dB(A) | Vibration Level |
|-----------|-----------------------------|----------------------------|-------------------|---------------------|--------------------|-------------------------|----------------------|
| S26145 | 3.0 - 5.9 (4-8) | 3/16" (M5) | 6,500 | 6.73" (171mm) | 2.2lbs (1.0kg) | 78 | <2.0m/s ² |
| S26146 | 3.7 - 7.4 (5-10) | 1/4" (M6) | 6,500 | 6.97" (177mm) | 2.2lbs (1.0kg) | 78 | <2.0m/s ² |
| S26148 | 5.9 - 11.8 (8-14) | 1/4" (M6) | 6,500 | 7.0" (178mm) | 2.2lbs (1.0kg) | 79 | <2.1m/s ² |
| S26149 | 11.1 - 22.1 (15-30) | 5/16" (M8) | 6,000 | 7.52" (191mm) | 2.8lbs (1.3kg) | 79 | <2.2m/s ² |
| S26150 | 16.2 - 33.2 (22-45) | 3/8" (M10) | 6,000 | 7.28" (185mm) | 3.3lbs (1.5kg) | 80 | <2.5m/s ² |
| S26151 | 25.8 - 47.9 (35-65) | 3/8" (M10) | 4,600 | 8.27" (210mm) | 4.2lbs (1.9kg) | 80 | <2.7m/s ² |

3/8" SQUARE PISTOL GRIP TORQUE CONTROL NON SHUT-OFF

| Model No. | Torque Range Ft-Lbs (Nm) | Bolt Capacity Inch (mm) | Free Speed RPM | Length Inch (mm) | Weight Lbs (kg) | Noise Level dB(A) | Vibration Level |
|-----------|-----------------------------|----------------------------|-------------------|---------------------|--------------------|-------------------------|----------------------|
| S26165 | 4.4 - 8.9 (6-12) | 1/4" (M6) | 6,500 | 6.02" (153mm) | 2.2lbs (1.0kg) | 78 | <2.1m/s ² |
| S26166 | 7.4 - 14.8 (10-20) | 1/4" (M6) | 6,500 | 5.79" (147mm) | 2.1lbs (0.97kg) | 78 | <2.0m/s ² |
| S26167 | 14.8 - 29.5 (20-40) | 5/16" (M8) | 6,500 | 6.02" (153mm) | 2.18lbs (0.9kg) | 79 | <2.1m/s ² |
| S26168 | 22.1 - 36.9 (30-50) | 3/8" (M10) | 6,000 | 6.38" (162mm) | 2.4lbs (1.1kg) | 79 | <2.2m/s ² |
| S26169 | 29.5 - 44.3 (40-60) | 3/8" (M10) | 6,000 | 6.34" (161mm) | 2.86lbs (1.3kg) | 80 | <2.5m/s ² |
| S26170 | 40.6 - 59.0 (55-80) | 1/2" (M12) | 4,600 | 7.24" (184mm) | 3.7lbs (1.7kg) | 80 | <2.7m/s ² |

* Torque Range (Hard Joint Rotatory Measure) @ 5 ~ 6 BAR (72.5 ~ 87 PSI)

Operating Air Pressure: 90 PSI / 6.2 bar.
Air Inlet Size: 1/4"

Safety Precaution: Read and follow all safety and operating instructions.

WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com
info@sabretools.com