


# SABRE AIRCRAFT TOOLS

## GENERAL PURPOSE MICROSTOP CAGE



Standard Type Skirt with Polished Foot

Model Number	Cutter Capacity inch/mm	Spindle Thread	Shaft Travel inch/mm	Max Speed RPM	Depth Adjustment inch/mm
S30121	9/16" (14.29)	1/4"-28	3/32" (2.38mm)	3,000	0.001" (0.0254mm)
S30125	9/16" (14.29)	M6x1	3/32" (2.38mm)	3,000	0.001" (0.0254mm)



Standard Type Skirt with Polished Foot

Model Number	Cutter Capacity inch/mm	Spindle Thread	Shaft Travel inch/mm	Max Speed RPM	Depth Adjustment inch/mm
S30220	1/2" (12.7)	1/4"-28	9/32" (7.14mm)	3,000	0.001" (0.0254mm)
S30225	1/2" (12.7)	M6x1	9/32" (7.14mm)	3,000	0.001" (0.0254mm)



Standard Type Skirt with Polished Foot

Model Number	Cutter Capacity inch/mm	Spindle Thread	Shaft Travel inch/mm	Max Speed RPM	Depth Adjustment inch/mm
S30320	5/8" (15.875)	1/4"-28	9/32" (7.14mm)	3,000	0.001" (0.0254mm)
S30325	5/8" (15.875)	M6x1	9/32" (7.14mm)	3,000	0.001" (0.0254mm)



Standard Type Skirt with Nylon Foot Piece

Model Number	Cutter Capacity inch/mm	Spindle Thread	Shaft Travel inch/mm	Max Speed RPM	Depth Adjustment inch/mm
S30321	5/8" (15.875)	1/4"-28	9/32" (7.14mm)	3,000	0.001" (0.0254mm)
S30326	5/8" (15.875)	M6x1	9/32" (7.14mm)	3,000	0.001" (0.0254mm)

**Safety Precaution:** Read and follow all safety and operating instructions.  
**WARNING:** Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com  
 info@sabretools.com