

SABRE AIRCRAFT TOOLS

Integrated Drill Countersink

- 5/8" Cutter capacity
- 9/32" Shaft Travel
- 0.001" increment adjustment
- Full ball bearing 10,000 RPM



S12318DAT Shown



S12340DAT Shown



SMX2PD 0.4HP (0.30Kw)						
Model Number	Free Speed RPM	Cutter Capacity inch/mm	Weight lbs/kg	Lenght inch/mm	Vibration Level	Sound Level dB(A)
S12304DAT	500	5/8" (16.0mm)	2.2lbs / 1.0kg	7.9" / 200mm	<2.5m/s2	83
S12303DAT	800	5/8" (16.0mm)	2.2lbs / 1.0kg	7.9" / 200mm	<2.5m/s2	83
S12321DAT	2,600	5/8" (16.0mm)	1.5lbs / 0.72kg	5.63" / 146mm	<2.5m/s2	83
S12318DAT	3,200	5/8" (16.0mm)	1.5lbs / 0.72kg	5.63" / 146mm	<2.5m/s2	83
S12317DAT	4,000	5/8" (16.0mm)	1.5lbs / 0.72kg	5.63" / 146mm	<2.5m/s2	83
S12316DAT	5,200	5/8" (16.0mm)	1.5lbs / 0.72kg	5.63" / 146mm	<2.5m/s2	83

SMX4PD 1.0HP (0.745Kw)						
Model Number	Free Speed RPM	Cutter Capacity inch/mm	Weight lbs/kg	Lenght inch/mm	Vibration Level	Sound Level dB(A)
S12340DAT	5,200	5/8" (16.0mm)	2.4lbs / 1.02kg	8.2" / 208mm	<2.5m/s2	83

Additional Models : Add "N" To End Of Part Number For Nylon No-Mar Foot Piece

Safety Precaution: Read and follow all safety and operating instructions.

WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.

www.sabretools.com • info@sabretools.com

