

SABRE AIRCRAFT TOOLS

90 Degree Angle Drills



SMX2AD Series 0.4HP (0.30KW) Rear Exhaust

Model Number Spindle Thread		Free Speed RPM	Weight lbs/kg	Length inch/mm	Side to Center Head inch/mm
1/4"-28	9/32"-40				
S15210	S15220	4800	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15211	S15221	3000	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15212	S15222	800	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15213	S15223	500	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15214	S15224	350	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)

SMX3AD Series 0.6HP (0.45KW) Rear Exhaust

Model Number Spindle Thread		Free Speed RPM	Weight lbs/kg	Length inch/mm	Side to Center Head inch/mm
1/4"-28	9/32"-40				
S15310	S15320	3800	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15311	S15321	2400	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15312	S15322	675	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15313	S15323	380	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15314	S15324	250	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)

Add XL to end of model number for extended reach head.

Eg: S15210XL

Part #SPA40015 (1/4-28)
#SPA40016 (9/32-40)

Standard Equipment
Safety Lever #SP15403SL



Vibration: < 2.5 m/s²
Noise Level: 80dBA
Air Inlet Size: 1/4"
Operating Air Pressure: 90 PSI / 6.2 bar.

Safety Precaution: Read and follow all safety and operating instructions.
WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com
info@sabretools.com