

SABRE AIRCRAFT TOOLS

45 Degree Angle Drills



SMX2AD Series 0.4HP (0.30KW) Rear Exhaust

Model Number Spindle Thread		Free Speed RPM	Weight lbs/kg	Length inch/mm	Side to Center Head inch/mm
1/4"-28	9/32"-40				
S15241	S15251	4800	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15242	S15252	3000	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15244	S15254	800	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15245	S15255	500	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15246	S15256	350	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)

SMX3AD Series 0.6HP (0.45KW) Rear Exhaust

Model Number Spindle Thread		Free Speed RPM	Weight lbs/kg	Length inch/mm	Side to Center Head inch/mm
1/4"-28	9/32"-40				
S15341	S15351	3800	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15342	S15352	2400	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15344	S15354	675	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15345	S15355	380	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15346	S15356	250	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)

Add XL to end of model number for extended reach head.

Eg: S15241XL

Part #SPA40030 (1/4-28)
#SPA40031 (9/32-40)

Standard Equipment
Safety Lever #SP15403SL



Vibration: < 2.5 m/s²
Noise Level: 80dBA
Air Inlet Size: 1/4"
Operating Air Pressure: 90 PSI / 6.2 bar.

Safety Precaution: Read and follow all safety and operating instructions.
WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com
info@sabretools.com