

SABRE AIRCRAFT TOOLS

360 Degree Angle Drills



SMX2AD Series 0.4HP (0.30KW) Rear Exhaust

Model Number Spindle Thread		Free Speed RPM	Weight lbs/kg	Length inch/mm	Side to Center Head inch/mm
1/4"-28	9/32"-40				
S15271	S15281	4800	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15272	S15282	3000	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15274	S15284	800	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15275	S15285	500	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15276	S15286	350	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)

SMX3AD Series 0.6HP (0.45KW) Rear Exhaust

Model Number Spindle Thread		Free Speed RPM	Weight lbs/kg	Length inch/mm	Side to Center Head inch/mm
1/4"-28	9/32"-40				
S15371	S15381	3800	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15372	S15382	2400	1.83lbs (0.83kg)	10.43" (265mm)	0.319" (8.1mm)
S15374	S15384	675	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15375	S15385	380	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)
S15376	S15386	250	2.2lbs (1.0kg)	11.81" (300mm)	0.319" (8.1mm)

Add XL to end of model number for extended reach head.

Eg: S15271XL



Standard Equipment
Safety Lever #SP15403SL



Vibration: < 2.5 m/s²

Noise Level: 80dBA

Air Inlet Size: 1/4"

Operating Air Pressure: 90 PSI / 6.2 bar.

Safety Precaution: Read and follow all safety and operating instructions.

WARNING: Face and eye protections must be worn while operating power tools, per

ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com

info@sabretools.com