

SABRE AIRCRAFT TOOLS

Pistol Grip Drills 0.4HP (0.30KW) & 1.0HP (0.745KW)



S12318



S12340



SMX2PD

0.4HP (0.30KW)

Model Number		Free Speed RPM	Drill Chuck Capacity inch/mm	Weight lbs/kg	Length inch/mm	Vibration Level	Sound Level dB(A)
Non Reversible	Reversible						
S12316		5,200	1/4" (6.35mm)	1.5lbs (0.72kg)	5.63" (148mm)	<2.5m/s ²	83
S12317		4,000	1/4" (6.35mm)	1.5lbs (0.72kg)	5.63" (148mm)	<2.5m/s ²	83
S12318		3,200	5/16" (8.0mm)	1.5lbs (0.72kg)	5.63" (148mm)	<2.5m/s ²	83
S12321		2,600	5/16" (8.0mm)	1.5lbs (0.72kg)	5.63" (148mm)	<2.5m/s ²	83
	S12330	2,000	5/16" (8.0mm)	1.5lbs (0.72kg)	5.63" (148mm)	<2.5m/s ²	83

SMX4PD

1.0HP (0.745KW)

Model Number		Free Speed RPM	Drill Chuck Capacity inch/mm	Weight lbs/kg	Length inch/mm	Vibration Level	Sound Level dB(A)
Non Reversible	Reversible						
S12340		5,200	3/8" (10.0mm)	2.24lbs (1.02kg)	8.2" (208mm)	<2.5m/s ²	83

Add the following termination to the model number for optional chuck.

Eg. S12317-10

- 10 No Chuck
- 15 Keyless 1/4"
- 20 Geared 3/8"
- 25 Keyless 3/8"

Air Inlet 1/4" NPT. Use 5/16" (8.0 mm) I.D. Hose.

Tool Performance rated @ 90PSI (620KPA) Air Pressure.

Safety Precaution: Read and follow all safety and operating instructions.

WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.

www.sabretools.com • info@sabretools.com

