

SABRE AIRCRAFT TOOLS

Pistol Grip Drills 0.6HP (0.45KW)



SMX3PD 0.6HP (0.45KW)

Model Number		Free Speed RPM	Drill Chuck Capacity inch/mm	Weight lbs/kg	Length inch/mm	Vibration Level	Sound Level dB(A)
Non Reversible	Reversible						
S12501		6,000	1/4" (6.35mm)	2.09lbs (0.95kg)	7.0" (185mm)	<2.5m/s ²	85
S12502		4,000	1/4" (6.35mm)	2.09lbs (0.95kg)	7.0" (185mm)	<2.5m/s ²	85
S12503		3,800	1/4" (6.35mm)	2.09lbs (0.95kg)	7.0" (185mm)	<2.5m/s ²	85
	S12504	2,100	3/8" (9.52mm)	1.00lbs (2.2kg)	8.5" (215mm)	<2.5m/s ²	85
S12505	S12506	700	3/8" (9.52mm)	3.08lbs (1.4kg)	9.9" (252mm)	<2.5m/s ²	85
S12507		500	1/2" (12.7mm)	3.08lbs (1.4kg)	9.4" (240mm)	<2.5m/s ²	85
	S12508	350	1/2" (12.7mm)	3.08lbs (1.4kg)	9.4" (240mm)	<2.5m/s ²	85

*Side handle included with all 1/2" models

Add the following termination to the model number for optional chuck.
Eg. 12501-10

-10 No Chuck	-30 Geared 1/2"
-15 Keyless 1/4"	-35 Keyless 1/2"
-20 Geared 3/8"	-40 Collet Chuck (specify collet size)
-25 Keyless 3/8"	

Air Inlet 1/4" NPT. Use 5/16" (8.0 mm) I.D. Hose.
Tool Performance rated @ 90PSI (620KPA) Air Pressure.

Safety Precaution: Read and follow all safety and operating instructions.
WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.

www.sabretools.com • info@sabretools.com

