

SABRE AIRCRAFT TOOLS

Pistol Grip Drills 0.8HP (0.60KW)



SMX3PD 0.8HP (0.60KW)

Model Number		Free Speed RPM	Drill Chuck Capacity inch/mm	Weight lbs/kg	Length inch/mm	Vibration Level	Sound Level dB(A)
Non Reversible	Reversible						
S12840		3,500	3/8" (9.5mm)	2.6lbs (1.2kg)	7.0" (185mm)	<2.5m/s ²	85
	S12841	2,400	3/8" (9.5mm)	2.6lbs (1.2kg)	7.0" (185mm)	<2.5m/s ²	85
	S12842	1,600	3/8" (9.5mm)	2.6lbs (1.2kg)	7.0" (185mm)	<2.5m/s ²	85
S12843		900	1/2" (12.7mm)	3.7lbs (1.7kg)	9.0" (230mm)	<2.5m/s ²	85
	S12844	700	1/2" (12.7mm)	3.7lbs (1.7kg)	9.0" (230mm)	<2.5m/s ²	85
S12845		600	1/2" (12.7mm)	3.7lbs (1.7kg)	9.0" (230mm)	<2.5m/s ²	85
	S12846	410	1/2" (12.7mm)	3.7lbs (1.7kg)	9.0" (230mm)	<2.5m/s ²	85
S12847		300	1/2" (12.7mm)	3.7lbs (1.7kg)	9.0" (230mm)	<2.5m/s ²	85
	S12848	220	1/2" (12.7mm)	3.7lbs (1.7kg)	9.0" (230mm)	<2.5m/s ²	85

*Side handle included with all 1/2" models

Add the following termination to the model number for optional chuck.

Eg. 12840-10

-10 No Chuck	-30 Geared 1/2"
-15 Keyless 1/4"	-35 Keyless 1/2"
-20 Geared 3/8"	-40 Collet Chuck (specify collet size)
-25 Keyless 3/8"	

Air Inlet 1/4" NPT. Use 5/16" (8.0mm) I.D. Hose
Tool performance rated @ 90PSI (620KPA) Air Pressure

Safety Precaution: Read and follow all safety and operating instructions.
WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com
info@sabretools.com