

SABRE AIRCRAFT TOOLS

Pistol Grip Drills



SMX4PD

0.9HP (0.67KW) Non-Reversible

Part No.	Free Speed RPM	Drill Chuck Capacity inch/mm	Weight lbs/kg	Length inch/mm	Vibration Level	Sound Level dB(A)
S13120	6,000	5/16" (8.0mm)	2.5lbs (1.15kg)	6.93" (176mm)	<2.5m/s ²	80
S13121	4,000	5/16" (8.0mm)	2.5lbs (1.15kg)	6.93" (176mm)	<2.5m/s ²	80
S13122	3,150	5/16" (8.0mm)	2.5lbs (1.15kg)	6.93" (176mm)	<2.5m/s ²	80
S13123	1,900	3/8" (9.5mm)	2.7lbs (1.23kg)	7.28" (185mm)	<2.5m/s ²	80
S13124	1,250	3/8" (9.5mm)	2.7lbs (1.23kg)	7.28" (185mm)	<2.5m/s ²	80
S13125	650	1/2" (12.7mm)	3.63lbs (1.65kg)	8.86" (225mm)	<2.5m/s ²	80

Add the following termination to the model number for optional chuck.

Eg. S13120-10

-10 No Chuck	-30 Geared 1/2"
-15 Keyless 1/4"	-35 Keyless 1/2"
-20 Geared 3/8"	-40 Collet Chuck (specify collet size)
-25 Keyless 3/8"	

Air Inlet 1/4" NPT. Use 5/16" (8.0mm) I.D. Hose
Tool performance rated @ 90PSI (620KPA) Air Pressure

Safety Precaution: Read and follow all safety and operating instructions.
WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.



www.sabretools.com
info@sabretools.com