

SABRE AIRCRAFT TOOLS

Pistol Grip Drills 1.0HP (0.745KW)



SMX4PD 1.0HP (0.745KW)

Model Number		Free Speed RPM	Drill Chuck Capacity inch/mm	Weight lbs/kg	Length inch/mm	Vibration Level	Sound Level dB(A)
Non Reversible	Reversible						
S12510		21,000	1/4" (6.35mm)	2.2lbs (1.0kg)	7.87" (200mm)	<2.5m/s ²	85
S12511		4,000	1/4" (6.35mm)	2.3lbs (1.05kg)	7.87" (200mm)	<2.5m/s ²	85
	S12512	3,800	1/4" (6.35mm)	2.3lbs (1.05kg)	7.87" (200mm)	<2.5m/s ²	85
S12513		3,300	3/8" (9.52mm)	2.4lbs (1.1kg)	8.58" (218mm)	<2.5m/s ²	85
	S12514	3,000	3/8" (9.52mm)	2.4lbs (1.1kg)	8.58" (218mm)	<2.5m/s ²	85
S12515		2,600	3/8" (9.52mm)	2.4lbs (1.1kg)	8.58" (218mm)	<2.5m/s ²	85
	S12516	2,000	3/8" (9.52mm)	2.4lbs (1.1kg)	8.58" (218mm)	<2.5m/s ²	85
S12517	S12518	1,000	1/2" (12.7mm)	3.3lbs (1.5kg)	9.05" (230mm)	<2.5m/s ²	85
S12519		600	1/2" (12.7mm)	3.3lbs (1.5kg)	9.05" (230mm)	<2.5m/s ²	85
	S12520	300	1/2" (12.7mm)	3.3lbs (1.5kg)	9.05" (230mm)	<2.5m/s ²	85

*Side handle included with all 1/2" models

Add the following termination to the model number for optional chuck.
Eg. 12510-10

-10 No Chuck	-30 Geared 1/2"
-15 Keyless 1/4"	-35 Keyless 1/2"
-20 Geared 3/8"	-40 Collet Chuck (specify collet size)
-25 Keyless 3/8"	

Air Inlet 1/4" NPT. Use 5/16" (8.0 mm) I.D. Hose.
Tool Performance rated @ 90PSI (620KPA) Air Pressure.

Safety Precaution: Read and follow all safety and operating instructions.
WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1

Products and specifications subject to change without prior notice.

www.sabretools.com • info@sabretools.com

