

SABRE AIRCRAFT TOOLS

Rivet Shaver Straight




SMX2SRS

0.0004" (0.010mm) Cutter Adjustment

Model No.	Skirt Diameter inch/mm	Free Speed RPM	Weight lbs/kg	Length inch/mm	Vibration Level	Sound Level dB(A)
S44031	1/4"	20,000	1.4lbs (0.64kg)	8.5" (215mm)	<2.5m/s ²	79
S44032	5/16"	20,000	1.4lbs (0.64kg)	8.5" (215mm)	<2.5m/s ²	79
S44033	3/8"	20,000	1.4lbs (0.64kg)	8.5" (215mm)	<2.5m/s ²	79
S44034	7/16"	20,000	1.4lbs (0.64kg)	8.5" (215mm)	<2.5m/s ²	79
S44035	1/2"	20,000	1.4lbs (0.64kg)	8.5" (215mm)	<2.5m/s ²	79
S44036	9/16"	20,000	1.4lbs (0.64kg)	8.5" (215mm)	<2.5m/s ²	79
S44037	5/8"	20,000	1.4lbs (0.64kg)	8.5" (215mm)	<2.5m/s ²	79

Optional Stabilizer Bar #SA44030

Rivet Shaver Cutters 1/4"-28 Thread									
SA44050 1/4"	SA44051 5/16"	SA44052 3/8"	SA44053 7/16"	SA44054 1/2"	SA44055 9/16"	SA44056 5/8"	SA44057 3/4"	SA44058 7/8"	SA44059 1"
		SA44152 3/8"		SA44154 1/2"					



14 Flute

Air Inlet 1/4" NPT. Use 5/16" (8.0mm) I.D. Hose
Tool performance rated @ 90PSI (620KPA) Air Pressure

Safety Precaution: Read and follow all safety and operating instructions.
WARNING: Face and eye protections must be worn while operating power tools, per ANSI B186.1



www.sabretools.com
info@sabretools.com